

## STANDARD MODELS

Model	Frequency Range	Output Power $P_N$ min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLMA 1025-75	1 ... 2.5 GHz	75 / 90	48.8 / 51 ±2	15 / 20	800	3 HU, 630 mm	22
BLMA 1025-150	1 ... 2.5 GHz	150 / 180	51.8 / 54 ±2	15 / 20	1000	3 HU, 630 mm	26
BLMA 1025-200	1 ... 2.5 GHz	200 / 250	53 / 55 ±2	15 / 20	1400	4 HU, 630 mm	32
BLMA 1025-250	1 ... 2.5 GHz	250 / 350	54 / 56 ±2	18 / 20	2000	4 HU, 630 mm	37
BLMA 1025-300	1 ... 2.5 GHz	300 / 350	54.8 / 57 ±2	15 / 20	2200	4 HU, 630 mm	37
BLMA 1025-500	1 ... 2.5 GHz	500 / 650	57 / 59 ±2	18 / 20	3500	9 HU, 630 mm	88
BLMA 1025-1000	1 ... 2.5 GHz	1000 / 1200	60 / 62 ±2	15 / 20	7000	12 HU, 800 mm	160
BLMA 1025-1500	1 ... 2.5 GHz	1500 / 1800	61.8 / 64 ±2	15 / 20	14000	17 HU, 630 mm	210

For individual data sheets, please click on the above model name

1 HU = 44.45 mm

## STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant)
	$P_N$ -0.5 dB min. at VSWR 2:1
Spurious (at $P_N$ ):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A-linear or AB-linear

## GENERAL

RF Input:	<12 GHz	N-f, standard on rear panel
	12 bis 18 GHz	SMA-f, standard on front panel
	>18 GHz	2.92 mm-f, standard on front panel
RF Output:	<12 GHz	N-f, standard on rear panel
	12 to 18 GHz	SMA-f, standard on front panel
	>18 GHz	2.92 mm-f, standard on front panel
Mains Supply:	Line Power:	
	Line Power	
	<800 VA	100 ... 240 V AC ±10%
	800 ... 3000 VA	200 ... 240 V AC ±10%
	>3000 VA	3x 400 V AC ±10%
Elapsed Time Meter:	via status display	
Ambient Temperature:	0 ... +45 °C	
Storage Temperature:	-20 ... +85 °C	
Relative Humidity:	up to 95% (non-condensing)	
Operating Altitude:	up to 2000 m above sea level	
Vibration and Shock:	MIL-STD-810 G	

# BLMA 1 ... 2.5 GHz Solid State Amplifiers

Cooling: forced air with integral blower  
air intake from front, air exhaust at rear

## OPTIONS

---

- |                                      |   |
|--------------------------------------|---|
| A) RF-Sample Ports *)                | L) LAN Remote Control                   |
| B) External Dual Directional Coupler | N) Harmonics Filtering *)               |
| C) IEEE-488.2 GPIB Remote Control    | R) RS-232C Remote Control               |
| D) Front Panel RF Connectors         | S) Internal RF Switching Unit *)        |
| E) RF Power Indication (digital) *)  | U) USB Remote Control                   |
| F) Gain Adjustment *)                | W) Liquid Cooling                       |
| G) Output Isolator *)                | X) External Control of other Amplifiers |
| H) DC Supply                         |   |
| I) 3x 208 V AC / 60 Hz               |   |

\*) These options may reduce output power and/or gain