

## STANDARD MODELS

Model	Frequency Range	Output Power $P_N$ min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BSA 0025-75	4 kHz ... 250 MHz				600	3 HU, 630 mm	16
	4 ... 9 kHz	30 / 40	44.8 / 48 ±3	15 / 10			
	9 kHz ... 250 MHz	75 / 100	48.8 / 51 ±2	20 / 20			
BSA 0025-150	4 kHz ... 250 MHz				700	3 HU, 630 mm	20
	4 ... 9 kHz	60 / 75	47.8 / 51 ±3	20 / 12			
	9 kHz ... 250 MHz	150 / 200	51.8 / 54 ±2	20 / 20			

For individual data sheets, please click on the above model name

1 HU = 44.45 mm

## STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant)
	$P_N$ -0.5 dB min. at VSWR 2:1
Spurious (at $P_N$ ):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A linear or A-B linear

## GENERAL

RF Input:	N-f, standard on rear panel
RF Output:	standard on rear panel
	<1 kW N-f
	<3 kW 7-16-f
	<5 kW EIA 1 5/8
Mains Supply:	Line Power:
	<1000 VA 100 ... 240 V AC ±10% / 47 ... 63 Hz
	1000 ... 3000 VA 200 ... 240 V AC ±10% / 47 ... 63 Hz
	>3000 VA 3x 400 V AC ±10% / 47 ... 63 Hz
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 G
Cooling:	forced air with integral blower air intake from front, air exhaust at rear

## OPTIONS

---

- |                                      |   |
|--------------------------------------|---|
| A) RF Monitor Outputs                | L) LAN Remote Control                   |
| B) External Dual Directional Coupler | R) RS-232C Remote Control               |
| C) IEEE-488.2 GPIB Remote Control    | S) Internal RF Switching Unit           |
| D) Front Panel RF Connectors         | U) USB Remote Control                   |
| E) RF Power Indication (digital)     | W) Liquid Cooling                       |
| F) Gain Adjustment                   | X) External Control of other Amplifiers |
| H) DC Supply                         |   |