

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BSA 0106-25/10D	9 kHz ... 6000 MHz				200	3 HU, 430 mm	24
	9 kHz ... 250 MHz	25 / 30	44 / 46 ±2	20 / 20			
	200 ... 1000 MHz	25 / 30	44 / 46 ±2	20 / 20			
	1000 ... 6000 MHz	10 / 15	40 / 43 ±3	15 / 20			
BSA 0106-25D	9 kHz ... 6000 MHz				250	3 HU, 630 mm	26
	9 kHz ... 250 MHz	25 / 30	44 / 46 ±2	20 / 20			
	200 ... 1000 MHz	25 / 30	44 / 46 ±2	20 / 20			
	1000 ... 6000 MHz	25 / 30	44 / 47 ±3	15 / 20			
BSA 0106-75D	9 kHz ... 6000 MHz				1000	3 HU, 630 mm	32
	9 kHz ... 400 MHz	75 / 85	48.8 / 51 ±2	20 / 20			
	400 ... 1000 MHz	75 / 85	48.8 / 51 ±2	20 / 20			
	1000 ... 6000 MHz	75 / 85	48.8 / 52 ±3	15 / 20			

For individual data sheets, please click on the above model name

1 HU = 44.45 mm

STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant)
	P_N -0.5 dB min. at VSWR 2:1
Spurious (at P_N):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A linear or A-B linear

GENERAL

RF Input:	N-f, standard on rear panel
RF Output:	standard on rear panel
	<1 kW N-f
	<3 kW 7-16-f
	<5 kW EIA 1 5/8
Mains Supply:	Line Power:
	<1000 VA 100 ... 240 V AC ±10% / 47 ... 63 Hz
	1000 ... 3000 VA 200 ... 240 V AC ±10% / 47 ... 63 Hz
	>3000 VA 3x 400 V AC ±10% / 47 ... 63 Hz
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level

BSA 9 kHz ... 6000 MHz Solid State Amplifiers

Vibration and Shock: MIL-STD-810 G
Cooling: forced air with integral blower
air intake from front, air exhaust at rear

OPTIONS

- | | |
|--------------------------------------|---|
| A) RF Monitor Outputs | L) LAN Remote Control |
| B) External Dual Directional Coupler | R) RS-232C Remote Control |
| C) IEEE-488.2 GPIB Remote Control | S) Internal RF Switching Unit |
| D) Front Panel RF Connectors | U) USB Remote Control |
| E) RF Power Indication (digital) | W) Liquid Cooling |
| F) Gain Adjustment | X) External Control of other Amplifiers |
| H) DC Supply | |