

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BSA 5001-1	500 kHz ... 1000 MHz	1 / 1.5	30 / 32 ±2	20 / 20	75	2 HU, 430 mm	11
BSA 5001-2	500 kHz ... 1000 MHz	2 / 2.5	33 / 35 ±2	20 / 20	75	2 HU, 430 mm	11
BSA 5001-5	500 kHz ... 1000 MHz	5 / 7	37 / 39 ±2	18 / 20	100	2 HU, 430 mm	11
BSA 5001-10	500 kHz ... 1000 MHz	10 / 12	40 / 42 ±2	20 / 20	150	2 HU, 430 mm	12

For individual data sheets, please click on the above model name

1 HU = 44.45 mm

STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant)
	P_N -0.5 dB min. at VSWR 2:1
Spurious (at P_N):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A linear or A-B linear

GENERAL

RF Input:	N-f, standard on rear panel
RF Output:	standard on rear panel
	<1 kW N-f
	<3 kW 7-16-f
	<5 kW EIA 1 5/8
Mains Supply:	Line Power:
	<1000 VA 100 ... 240 V AC ±10% / 47 ... 63 Hz
	1000 ... 3000 VA 200 ... 240 V AC ±10% / 47 ... 63 Hz
	>3000 VA 3x 400 V AC ±10% / 47 ... 63 Hz
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 G
Cooling:	forced air with integral blower air intake from front, air exhaust at rear

OPTIONS

A) RF Monitor Outputs	L) LAN Remote Control
B) External Dual Directional Coupler	R) RS-232C Remote Control

BSA 500 kHz ... 1000 MHz Solid State Amplifiers

- C) IEEE-488.2 GPIB Remote Control
- D) Front Panel RF Connectors
- E) RF Power Indication (digital)
- F) Gain Adjustment
- H) DC Supply
- S) Internal RF Switching Unit
- U) USB Remote Control
- W) Liquid Cooling
- X) External Control of other Amplifiers